

	M ROADSTER M COUPE	Z3 2.5, 3.0 roadster/coupe	325i, 330i	M3	5 SERIES (EXCL. M5)	M5	740 i / iL	750 iL	Z8	✓
TECHNICIAN'S SIGNATURE	E36	E36	E46	E46	E39	E39	E38	E38	E52	
For BMWs Engine Oil Service										
Change oil and oil filter while engine is at operating temperature. We recommend High Performance 5W-30 Synthetic oil, p/n 07 51 0 017 866		●	●		●	●	●	●	●	
Change oil and oil filter while engine is at operating temperature. Use only Castrol TWS Motorsport SAE 10W-60 Synthetic oil, or Castrol Formula RS 10W-60 Synthetic oil, p/n 07 51 0 009 420	●			●						
Replace microfilters. Note: reduce replacement interval in dusty operating conditions.			●	●	●	●	●	●	●	
Check overall thickness of front and rear disc brake pads using special tool. Record results. If replacement is necessary*: Examine brake disc surfaces. Clean brake pad contact points in calipers. Grease wheel centering hubs. Check thickness of parking brake linings only when replacing rear pads. Record results.		●	●	● rear only	●	●	●			
Remove and install front and rear disc brake pads, check overall thickness. Record results. Examine brake disc surfaces. Clean brake pad contact point in calipers. Grease wheel centering hubs.	●			● front only				●	●	
Check parking brake actuation. Adjust if necessary.	●	●	●	●	●	●	●	●	●	
Reset Service Indicator. Note: Do not reset Service Indicator when additional oil changes (between the normal intervals) are requested by the customer.	●	●	●	●	●	●	●	●	●	

